

## Mitech MEW Micro Control Series Hydraulic Universal Testing Machine

### Overview

Mitech MEW Micro Control Series Hydraulic Universal Testing Machine through controlling high pressure oil pump to drive screw motion, equipped with corresponding auxiliary equipment for metal, nonmetal and composite materials tensile, compression, bending, shear, peel, tear and other mechanical properties test, its clearance seal oil cylinder with high precision, computer display technology, digital processing, high precision data acquisition control technology, its performance is stable, powerful functions, the data processing accurate, is solid in construction, simple structure, high reliability, simple operation, friendly interface. Widely used in metal and non-metallic processing and manufacturing, quality inspection department quality inspection, institutions of higher learning, scientific research test, and other fields, it is to improve the production efficiency, save production costs necessary professional precision testing instrument.

### Technical Parameters

Technical parameters	MEW			
	MEW-100	MEW-300	MEW-600	MEW-1000
Structural framework	Gate type			
Maximum testing force (KN)	100	300	600	1000
Indicated error	Better than $\pm 1\%$ of the indicated value			
Force measuring range	4%-100% of Maximum testing force			
Deformation precision	$\pm 1\%$			
Clamping type	Manual clamping		Manual /Automatic clamping	
Circle sample holder diameter	$\Phi 6-26\text{mm}$	$\Phi 10-32\text{mm}$	$\Phi 13-40\text{mm}$	$\Phi 26-60\text{mm}$
Flat specimen clamping thickness	0-15mm	0-15mm	0-30mm	0-40mm
Diameter of the shear sample	10			
Size of upper and lower plate	$\Phi 160$			
Stretch space	550mm		650mm	
Compression space	$\geq 500\text{mm}$			
Protect Function	Overload protection, limit protection			
Power supply	380V ( Three phase four wire system )			
Clamp form	Suitable clamps will be configured according to the customer requirements.			

	Special clamps can be customized for the customer.			
Dimensions(mm )	940*680*2000		1000*640*2400	1130*1230*2700
Total weight	1200kg	1200kg	2000kg	3000kg

## Working Principle

The testing machine is the product of combining the testing machine technology with the mechanical transmission technology, the sensor technology, the automation control technology and so on, which is composed of the drive system, the control system, the measurement system. The driving system is mainly used for the movement of the beam of the testing machine through the control valve. The control system regulate the testing machine by the console, getting the state of the test machine and the test parameters through the display screen. The measuring system can conduct the measurement of force, deformation and beam displacement using the sensor, signal amplifiers, photoelectric encoders and data processing systems. This machine can conduct the mechanical performance testing of the material pull, pressure, bending and so on through the coordination of the drive system, control system, measurement system and other subsystems.

## Features

- Widely used in metallic and non-metallic processing industry, quality testing in quality inspection departments, scientific research in higher education institutions and other fields;
- Integrated oil source design makes the whole structure more compact and reasonable, reducing the area;
- Having functions of displaying test force, testing force peak, testing force rate and others;
- Using 5000-line optoelectronic encoder, with relative high accuracy of displacement;
- Using high precision and high stability sensor, with high precision measurement and amplification system to ensure that the test force of high precision;
- Built-in controller to ensure that the test machine can be specimen deformation, test force and displacement of the closed-loop control;
- Having a limit protection function, arrived at the limit after the automatic shutdown, to prevent the collision in the middle of the beam caused by overload or even damage to the sensor;
- A variety of customization, to meet the needs of a variety of materials testing;
- PCI-based built-in control card, can reduce the connection, improve the test real-time control and real-time acquisition function, improve product stability;
- Can choose the load sensor or oil pressure sensor, effectively improve the test range and force value accuracy;
- Automatically according to the size of the load can be switched to the appropriate range to ensure the accuracy of measurement data;
- Zero adjustment, calibration, storage, etc. without any analog adjustment link, the control circuit is highly integrated;
- Test end, test data and test curve automatically saved for later retrieval analysis;
- Can be batch test, the same parameters of the sample only a test set;
- Consistent with GB, ISO, ASTM, DIN and other relevant domestic and foreign standards.

## Scope of application

Widely used in pull, pressure, bending and other mechanical properties test of metal, non-metallic and composite materials;

## Applications

- Quality control link of Metal processing manufacturing
- Quality control link of nonmetal manufacturing industry
- Teaching experiment of scientific research in Institutions of higher learning
- Material analysis test of scientific research institutions
- Quality inspection link of Quality inspection department

## Working Conditions

- Operation Temperature: Ambient temperature ~45°C;
- Relative humidity: 20% ~ 80%;
- In an environment free from vibration, corrosive medium and high magnetic field;
- Installed on a flat basis;
- Power supply voltage fluctuation does not exceed 10% of rated voltage.

## Configurations

Configuration instructions	NO.	Name	QTY.	Remarks
Standard Configuration	1	Testing machine host (Gap seal cylinder)	1	Contains sensor, limit
	2	control system	1	
	3	Piano desktop screen dedicated oil source	1	
	4	Manual return valve	1	
	5	Dual Channel Programmable Amplifier	1	
	6	High precision oil pressure sensor	1	
	7	Photoelectric encoder	1	
	8	Flat jaws	1	0-15mm
	9	Round jaws	2	13-26mm、26-40mm Each pair
	10	Extensometer	1	
	11	Computer	1	Display device
	12	Printer	1	HP A4 inkjet printer
Optional Configuration	1	Auxiliary		Customized according to customer requirements

## Maintenance and care

- Test machine is a large precision instruments, should pay attention to water, moisture. Exposed workstations, upper and lower beam parts and attached parts should be coated with anti-rust oil to prevent rust;

- If idle for a long time, move the upper and lower beams at least once a week so that preventing the beam position, silk mother from rust;
- long-term frequent use may lead to oil reduction or deterioration, check the amount of oil based on the use every 1 to 3 months, when the oil level is below the oil window, add the same kind of hydraulic oil to the middle of the window; if the oil has deteriorated, unscrew the oil source after the lower oil nozzle, then release and replace of hydraulic oil;
- Frequent use of this equipment for tensile failure test may make some fasteners loose.
- The following parts should be checked often for tightening :
  - ① the upper beam and moving beams before and after each have two (a total of 8) L-type pressure plate (with a jaw card board guide role), each plate with three screws fixed;
  - ② move the cross beam at both ends of the six screws;
  - ③ check the degree of tightness of the screw drive chain every 6 months, the corresponding adjustment of the tension wheel position (need to remove the main body under the hoarding);
- According to the environmental conditions and frequency of use, lubricate the following parts every 3 to 6 months:
  - ① the combining areas of screw and the base of the junction, using 100 oil lubrication (need to remove the main body under the hoarding);
  - ② screw drive chain, using butter (need to remove the main body under the hoarding);
  - ③ keep the screw thread part clean and lubricated with butter or molybdenum disulfide;
- There are two jaws on the upper beam and the moving beam, which is the important part of the machine. Clear the debris on the contact surface of the jaw and the beam often, and remove the side of the moving beam of the platen, remove the jaw card board, clear the jaw card plate and beam contact surface with oil wipers, coated with appropriate amount of butter and graphite mixed grease, install the jaw card board and tighten the screws of pressuring plate;
- Do not click "start test" button before starting the test, it's easy to cause accidents;
- When entering the program, if the abnormal prompt or the default test force value is different from the past, do not test, exclude referring to the troubleshooting method;
- If the program does not exit the test state after the test is broken, immediately click [Stop] to exit the test state;
- After completing the test exit procedure, the cylinder must fall to the end to shut down the pump;
- The software has overload protection function, when the load is more than 0.2% of full scale, there will be a protective prompt, please press OK and stop the experiment;
- Don't disassemble the instrument without authorization, maintenance related matters please contact MITECH after-sale service department with 4000600280.